



大榮工業股份有限公司

Great Winexpress Industrial (Holdings) Company Limited

香港上環文咸東街79-85號文咸中心901室
Room 901, Bonham Centre,
79-85 Bonham Strand East,
Central, Hong Kong.

Tel : 2545 6068 2541 1114 (5 Lines)
Fax : 2854 0404 2544 3157
E-mail : greatwin@hkstar.com

Product Specification

A-HM30 / A-WM30

Hand lay-up Surfacing Veil / Winding Surfacing Veil

Characteristics

Surfacing veil is mainly used in the surface layers of FRP products. It is divided into winding A-WM series and hand lay-up A-HM series. WM are mainly used on pipe and tank winding process. It can improve the product surface property on corrosion resistance, compressive strength, seepage resistance and longer service life.

HM is chiefly used in the product with complicated geometric curve. It has the advantages of good pattern fitness, quick resin permeation. It can raise the intensity and corrosion resistance of products and it has the below excellent performance:-

- Excellent fiber distribution
- Smooth surface appearance of finished products
- Corrosion resistant
- Low binder content
- Good molding properties

Specifications

Test Item	Unit	Standard(HM)	Standard(WM)
Area Weight	G/m ²	30±4	30±4
Binder Content	%	6.0	8.0
Tensile Strength MD	N/50 mm	≥20	≥25
Moisture Content	%	0.2	0.2
Color	White		

Packing and Storage

Surfacing tissue is wound onto a paper tube and wrapped up with plastic film, which can be wrapped up with kraft paper. The rolls are be vertical placed.

Products shall be placed under dryness condition and the covering membrane shall be no opened until applying.